

# Analysis of Mobility Management for Vertical Handover in Heterogeneous Wireless Networks

<sup>1</sup>Mr. Piyush K Ingle, <sup>2</sup>Dr. M. V. Sarode, <sup>3</sup>Dr. Meenakshi Arya

<sup>1,3</sup>G. H. R.C .E, Nagpur, MH, India

<sup>2</sup>Government Polytechnic, Yavatmal, MH, India

Email: [piyush.ingole@raisoni.net](mailto:piyush.ingole@raisoni.net)

Received: 09<sup>th</sup> July 2018, Accepted: 14<sup>th</sup> August 2018, Published: 31<sup>st</sup> August 2018

## Abstract

With the expanding domains of the wireless technologies the mobility offered by the system is usually expanding providing users to be able to move between various networks simultaneously. Since the mobility in heterogeneous wireless techniques, vertical handovers are very much more advanced than the conventional horizontal handovers used. Inside IEEE 802. 21 a new platform for a standard addressing a uniform and media independent framework is used for seamlessly handover between different technologies. It is known as Media Independent Handover (MIH). In past many years lot of research offers been completed for improving the handover between various access technologies. In this specific paper, we are proceeding to illustrate various handoff techniques implemented in typically the past. A comparative view proposes the efforts from the technique and their advantages and disadvantages.

**Keywords:** Media Independent Handover, Handoff Techniques, IEEE 802.21.

## Introduction

Typically the impression of Next Technology Wireless Networks will depend on typically the concurrence and the interoperability of various kinds of Radio stations Access Technologies (RATs), regarding example, GSM, UMTS, LTE, and WiMAX has recently been brought to bolster the connection system present. Vertical handover management is one regarding the significant constraints to ensure steady range of motion keeping in mind the end goal to accomplish productive asset usage and keep up service quality. The cutting edge remote systems are relied upon to bolster the consistent vertical handoff component in which clients can keep up the associations notwithstanding when they change starting with one system then onto the next with management progression.

IEEE 802. 21 provides a provides which encourages consistent handoff in heterogeneous remote systems. It is a way to deal with improvements of these handover techniques through a novel IEEE 802. 21 Media Independent Handover standard gives the innovative cynic system to get cross layer control data of system condition. The purpose of this project is to analyze a productive vertical handover technique in view of

IEEE 802. 21 models for best nature of service to an extensive variety of utilizations.

The handover situation is utilized to assess the vertical handover execution including a multimode terminal with WiFi /WiMAX interfaces and IEEE 802. 21 elements. The strategy will also consider the connection layer and application layer data and settles on choices relying upon that data.

It will enable the remote terminals to be constantly associated and also provide consistent portability in vertical handoff. The overview strategies are looked from the current strategies. Fun result demonstrates that typically the likelihood of handover frustration and superfluous handover regarding the proposed strategy usually are limited by considering typically the speeds of network hubs. IEEE802. 21 - Media Independent Handover (MIH) starts working in addition to build up a regular method to inspire vertical handover in the heterogeneous systems [5]. It characterizes a new conceptual system that enhancements and enhances handover delivery by giving data concerning the connection layer breakthroughs to the higher tiers. The goal of such provisioning is usually to accomplish low-inactivity handovers also to provide insight inside system choice.

However, MIH does not consider factors to make handoff and locate target of any network virtually [1]. Also, the MIH structure is usually a general system; it should be included with the particular techniques to enhance the mobility in different domains, considering an approach between inter-technology handover processes.

MIH in Handover:

Typically the MIH uses Mobility methods at different layers in the protocol stack to supply the support of range of motion inside the networks available. To be able to add the mobility inside network layer techniques just like MIPv4, MIPv6, FMIPv4 and so forth. are implemented. In this specific section we are proceeding to discover many these kinds of techniques:

MIP in IP:

MIPv4 is one of typically the acclimatized conventions advised to be able to accord the arrangement transportability to IPv4.

In MIPv4, two sorts of professionals accept been characterized with Home Agent (HA) will be the abettor in the MN's home

arrangement and Overseas Agent (FA) is typically the consultant inside the visited agreement by the system. Every MN acquires a abiding home (personal residence) at no matter what point it registers together with it's HA. Likewise, a great MN gets a Proper care of Abode (CoA) extra than its claimed house, which is not stable and changes as MN goes amid alfresco methods. CoA shows the MN's present breadth and is usually gotten from FA. MNs can admit whether they will accept confused to over subnet by agency regarding affability into Agent Ad letters beatific by FAs. Additionally, MNs can request for Advertisement letters using Agent Solicitation messages. At this stage if a adaptable center gets new CoA (FA-CoA) from advance messages, that registers with HA concerning the new breadth (new CoA). Quite some time later, the suggestions accoutrements the abstracts of which are beatific from typically the Correspondent Node (CN) to be able to the home system, that is handed-off to MN's, which often as well went by a system using a access from ANORDNA for the new FA [11]. The HA might accord the CoA in order to the sender of guidance bundles with the finish ambition that approaching accoutrements be burrowed to the particular FA specifically. Fig. one demonstrates the MIPv4 procedure when the agreed MN techniques from its home arrangement in order to the outside system.




Figure 1: MIPv4 Mobility Management

Among the issues with MIPv4 will be that if an MN details abject in the awning breadth amid two systems, taking ad letters from each the systems accompany regarding ping-pong appulse[12]. M. -M. Kim, J. -W. Jang [12], within Low cessation vertical handover application MIH L2-Trigger formula in adaptable IP Networks of [12] take activated MIH to wear the ping-pong appulse simply by auctioning requesting/notice action making use of a mix of Hyperlink

Heading down (LGD) contest plus MIIS advancements. To strategy the move from house adjustment to alfresco program, HA gets abstracts regarding the new reach the network (address of FA) via MIH\_Get\_Information primitive. When this occurs in case LGD accident happens, MN asks for this abstracts from HA and works MIP acceptance through approved PoA in the designated interim. At last, L2 handover towards the new PoA is an expert afterwards enrollment. This action lessens the particular handover cessation and variety disturbance; the author has not really audibly depicted the way the MN recognizes the hopeful FA amid the adjoining techniques (FAs) to accomplish pre-enlistment. Likewise, they accept not really advised the awning bearings if MN navigates starting with one alfresco adjustment anew assimilate the next restricted system.


Fast MIPv4 (FMIPv4) is inclusion assemblage apparent in RFC 4988 by C. Perkins [13] for adjustment music group advancement to abate the particular MIPv4 handover inactivity. This particular depends upon the quick handover action broadcast in RFC 4068 as bidding within, Enhanced FMIPv4 accumbent handover with minimized approach checking time based on Press Independent Handover (MIH) simply by [14] Nited kingdom. Byung-Kil, J. Young-Chul, We. Kim, K. Young-Tak [14]. FMIPv4 gives the particular encompassing adjustment adjacency abstracts to ensure that a adaptable centre can adjudge if this is affective to inclusion subnet even afore the particular handover [13].

Within this prescient mode, MN causes Fast Binding Update (FBU) bulletin to the completed Admission Router (pAR) above abutting to the fresh Admission Router (nAR). This specific action happens afterwards Router Solicitation for Proxy Ad (RtSolPr) and Proxy Router Advertisement (PrRtAdv) letters having traded amidst MN in addition to pAR, from breadth MN can get abstracts about new admission switch. Subsequently in the alertness of FBU message, pAR sets up an official amid accomplished CoA (pCoA) and nAR's IP abode in its administering table (a bidirectional admission amidst pAR and nAR is set up trading HI/Hack messages) to advanced bundles to nAR while L2 handover is in beforehand and along pAR restores a FBack bulletin to MN. The MN sends the FBU afresh paying little heed to its accomplished manual if affiliated to the new PoA is recognized. This enables nAR to analyze carriageable hub's affiliation and also to activate sending absorptive parcels. This retransmission of FBU is additionally attainable if an FBack has not been gotten yet in ablaze of accomplished FBU (receptive mode) [13]. As against to clear-sighted mode, in a receptive mode, MN triggers FBU bulletin to nAR afterwards L2 handover to addition get to adapt (after disengagement from the old adjustment and associated with the new one) [14].

In this particular prescient mode, MN leads to Fast Binding Update (FBU) bulletin to the finished Admission Router (pAR) over abutting to the new Admission Router (nAR). This particular specific action happens later on Router Solicitation for Proxy server Ad (RtSolPr) and Proxy server Router

Advertisement (PrRtAdv) characters having traded amidst MN in addition to k?rester, from breadth MN may get abstracts about brand new admission switch. Subsequently within the alertness of FBU message, pAR sets up a good official amid accomplished CoA (pCoA) and nAR's IP abode in its giving table (a bidirectional entrance amidst pAR and nAR is placed trading HI/Hack messages) to advanced bundles in order to nAR while L2 handover is within beforehand and together pAR restores a FBack bulletin to MN. The particular MN sends the FBU afresh paying little attention to its accomplished guide if affiliated to the particular new PoA is acknowledged. This allows nAR in order to analyze carriageable hub's association and also to trigger sending absorptive parcels. This particular retransmission of FBU will be additionally attainable if a good FBack has not already been gotten yet in enlightened of accomplished FBU (receptive mode) [13]. Because against to clear-sighted setting, in areceptive mode, MN triggers FBU bulletin in order to nAR afterwards L2 handover to addition get in order to adapt (after disengagement through the old adjustment plus associated with the brand new one) [14].

MIPv6 is perceived as inclusion common adjustment that can bolster carriageable administrations amid altered admission systems as proposed by Y. -Y. A K. -W. Lee, D. -W. Kum, S. H. Lee, Y. -Z. Cho, B. Yae, W. -Y. Jungin [15]. MIPv6 underpins handover if MN moves to addition IPv6 subnet. The MIPv6 handover alignment comprises of three stages as appeared in Fig. 2 . The capital date is development analysis performed afterwards L2 handover to addition PoA in addition subnet. In this stage, MN finds addition get to about-face (nAR) from about-face ad messages. This bulletin contains IP prefix, interface band address, and added abstracts about the new get to arrange. The additional date is CoA design. In this stage, new CoA will be fabricated with account to the IP prefix of the new adjustment and Duplicate Abode Detection (DAD) adjustment will be performed/onto affirm its character in the new system. The endure date is Binding Update (BU) abode to admonish the HA and Correspondent Node (CN) about new CoA. Back the majority of the techniques are performed afterwards L2 handover to the new get to organize, the dawdling of MIPv6 handover is all-encompassing and influences affair congruity.



FMIPv6 [16] which has been illustrated in IETF MIPSHOP can abate the handover cessation of MIPv6 [17]. FMIPv6 is advised to yield out postponements with development location, CoA arrangement, and admission foundation like FMIPv4. Doing such a, MN needs to apprehend its IP

advancement and this requires interface band triggers for handover foresight. Afterwards foresight, pAR is in allegation regarding clearing the adjustment word of nAR as each L2 identifier appear inside affiliation band trigger. MN sends L2 identifier inside RtSolPr bulletin for the dole and pAR reacts together with PrRtAdv bulletin including home abstracts of applicative nAR. At whatever point MN is accomplished in the nAR's prefix, it frames nCoA and sends an FBU bulletin to its dole to set up a new admission afore the L2 handover to new acquire to adapt happens. A new while later, MN may possibly get the FBack bulletins on the present connection which implies that bindle burrowing amid the artery amount and nCoA is usually in advance. Being out these lines, MN could forward UNA array to be able to ask for cradled accoutrements afterwards L2 handover to be able to new PoA. The FMIPv6 may also plan in a new acknowledging approach area FBU is beatific afterwards L2 handover for the new acquire to arrange. One of many total issues with FMIPv6 is the fact affiliation band triggers turned on for suspicion accept not necessarily been bent in typically the standard.

Writers B. Mussabbir, Y. Wenbing, N. Zeyun, F. Xiaoming, Optimized FMIPv6 application IEEE 802. 21 MIH casework in vehicular networks [17] accept suggested avant-garde MIPv6 and FMIPv6 handover action utilizing MIH administrations. They accept offered an IE alcove within MIIS that food L2 and L3 abstracts associated with adjoining admission systems. This particular abstracts has been acclimated to belch the obtain to about-face acknowledgment adjust (RtSolPr/PrRtAdv) in FMIPv6. These people additionally accept proposed the adjacent assets in MNs to brief abundance the particular abstracts about adjoining techniques that abate the abstracts get to time. Within their strategy, an adjusting motor (PE) has already been installed in MNs that will utilizations QoS ambit through attainable systems, and together QoS prerequisites of utilizes to attain on a severe handover choice. Getting in order to QoS aliment of utilizations, new MICS and MIES primitives (called MIH\_App\_Req plus MIH\_App\_Parameters) accept been recognized in [17].

To gain access to activating QoS ambit regarding hopeful get to methods, the cardboard has transmitted the limited MICS simple, i. e. MIH\_MN\_HO\_Candidate\_Query, to be able to absorb a briefing regarding asked for ambit (e. g. throughput, bindle postpone, and so on. ) in 'Inquiry Resource List'. The PE sends this specific analysis to Confined PoA and it utilizes The MIH\_N2N\_HO\_Query\_Resource adjustment to catechism in addition to set the attainable resources of appellant PoAs. From last, MIH\_MN\_HO\_Cadidate\_Query. answer is usually appear aback to MN from confined PoA. Coming from that point, MN decides about new get to be able to network, utilizes L3 home abstracts of chose to be able to get to thenetwork to be able to anatomy nCoA and directs FBU bulletin to their absence about-face (pAR) [17].

Writers of [17] accept congenital up the amusement bureaucracy utilizing NS2 align analysis adjustment in order

to authenticate the beheading of the proposed technique. The enjoyment action incorporates a WiMAX and a WiFiPoA along with 1000 m and fifty m ambit ranges, individually. A multi-interface MN along with two applications (video plus sound) has been beheld as that moves reality at an approximate speed in the around associated with 5 and 25 m/s in normal. Reproduction comes about accept approved that the particular proposed address has underneath concerning the bisected of the particular handoff dawdling of FMIPv6 for both applications within normal.

2.2. Employing MIH in SCTP-based mobility management  
Flow Control Transfer Protocol (SCTP) is a assemblage that will was planned since a good IP buggy assemblage along with changed attributes, as an example, multi-gushing in addition to multi-homing backing. The certain assemblage has been developed by SIGTRAN IETF still living purchase and has recently been institutionalized as RFC 4960 [18]. SCTP allows 2 end-hosts to physique upward a affair in addition to dicker an adjustment regarding modified IP addresses. Virtually any associated with these IP places may again end up being activated in order to be able to barter advice bundles, which often usually offers advice regarding multi-homing [19]. Right now there usually are two sorts regarding the actual manual strategies a great association, specifically, capital as well as accretion way. The major city method is the principal guide way, and typically the other men and women are accretion ways. Upon the away from adventitious that will typically the capital way will probably be busted, the manual will modify to a accretion approach [20]. A pair of augmentations accept recently been suggested on SCTP, regarding instance, Dynamic Abode Reconfiguration (DAR) [21] plus able SCTP [21] that fake this portability empowered. Typically the Powerful Abode Reconfiguration ?rsberetning brands addition section range supposed ASCONF. It may be activated by a great endpoint to authenticate their accessibility through addition IP provide or to physical appearance which will it is not really achievable by agency associated with the aforesaid answer 1. Addition equipment of ASCONF is to announce which usually adjacency IP abode treatment to become activated by the particular associated being an capital method [22]. Versatile SCTP has additionally been suggested as portability empowered option of SCTP. As putting in a bid some time recently, SCTP turns into a flexibility empowered carriage assemblage along with DAR expansion. Able SCTP depends upon DAR accession plus proposes to accord additional account which will enable choices anecdotic with; in case to physically affix along with a PoA, IP bureaucracy of the accustomed link, the amplification of the particular since backward abiding in order to affix to a recognized affiliation, and architecture regarding a limited amalgamation since capital way.

Authors regarding [20] acknowledge abolished a allocation regarding the MIES primitives to boost the beheading of handoff in an SCTP-based in a position VoIP framework in a new area organize. They adjusted Link Still dropping break to

be able to change the capital approach (SET PRIMARY) afore handover all-overs out at abbreviating the array misfortune.

About access of Link Lower occasion, the IP home of the appliance software is expelled (DELETE IP) and afterwards cleanup regarding the handover, the fresh IP abode is roofed (ADD IP) to the relationship. In [30], the actual beheading of utilizing Web page Heading down break inside SCTP handover continues to be able to be advised plus various and accepted technique. Typically the accepted way merely by which often way disappointment will probably be entretejer depends on the astigmatisme counter. This undesirable which often is kept with consider to anniversary of typically the attached endpoints is extra loved-one's birthday time a range alarm system lapses or when the beatific beating is definitely not acknowledged. At typically the point when the affection of aberration adverse exceeds the Path Maximum Retransmission (PMR) parameter, a method disappointment is distinguished. Writers accept adjourned the beheading of utilizing LGD with regard to way exchanging by a few NS2 recreations. The mimicked action is anchored simply by WiMAX and HSDPA obtain to systems and 2 multi-homed hubs barter FTP movement amid them. The particular WiMAX amalgamation may be the funds way, while HSDPA user interface speaks to the accretion way. The reenactment comes about accept approved that making use of LGD performs above in order to accepted action beneath numerous PMR esteems apropos variety misfortune.

### Analysis & Conclusion

Within this segment, a relative lowdown of representative strategies introduced in this paper is introduced. This outline discussions about the normal patterns and furthermore contrasts in a portion of the strategies spoken to in several regions of MIH work. This area depends on a rundown on work of MIH to enhance the execution of mobility management strategies. The lowdown of some illustrative techniques are mentioned in Segment 2. An examination of strategies that can be used to enhance the execution of MIP family demonstrates that dispensing with the be able to switch disclosure is the essential change in these techniques (aside from PMIPv6 which would not require getting to switch revelation). MIIS is utilized to get L3 data of hopeful get to arrange rather than revelation methodology. Additionally, Website link Going down (LGD) occasion is habitually used to demonstrate the handover strategy in these strategies. Examining for accessibility of resources in competitor be able to organise is another imperative take note which merely a portion of the works.

Contrasting the strategies that utilize the MIH to enhance the execution of SCTP demonstrates that LGD is ordinarily utilized for quick development identification and essential way change. Additionally, the proposed enhancements on SIP have misused LGD to precede the handover method. Likewise, MIIS has been used in a portion of the SIP-based versatility administration strategies to get data about neighboring access systems which are utilized for target choice. A typical

deficiency with the vast majority of the enhancements in portability administration conventions is the absence of the objective determination computation.

### References

- [1] Kumar, Vimal, and NeerajTyagi. "Media Independent Handover for Seamless Mobility in IEEE 802.11 and UMTS based on IEEE 802.21." Computer Science and Information Technology (ICCSIT), 2010 3rd IEEE International Conference on. Vol. 4. IEEE, 2010.
- [2] Kumara.u "Vertical Handover in Vehicular Ad-hoc Networks – A Survey" International Journal of Latest Trends in Engineering and Technology (IJLTET)- Vol. 3. Issue 4 March-2014, PP 132-138.
- [3] Yan, Xiaohuan, Y. Ahmet Şekercioğlu, and Sathya Narayanan. "A survey of vertical handover decision algorithms in Fourth Generation heterogeneous wireless networks." Computer Networks 54.11 (2010): 1848-1863.
- [4] Li, Mo. Handover mechanisms in next-generation heterogeneous wireless networks. Diss. University of Technology, Sydney, 2008.
- [5] IEEE Standard for Local and metropolitan area networks - Part 21: Media Independent Handover Services.
- [6] I.F. Akyildiz, X. Jiang, S. Mohanty, A survey of mobility management in next generation all-IP-based wireless systems, IEEE Wireless Communications 11 (2004) 16–28.
- [7] J.-M. Kim, J.-W. Jang, Low latency vertical handover using MIH L2-Trigger algorithm in mobile IP Networks, in Parallel and Distributed Processing and Applications, 2007, pp. 707–718.
- [8] C. Perkins, RFC 4988; Mobile IPv4 Fast Handovers, IETF, 2007.
- [9] K. Byung-Kil, J. Young-Chul, I. Kim, K. Young-Tak, Enhanced FMIPv4 horizontal handover with minimized channel scanning time based on Media Independent Handover (MIH), in Network Operations and Management Symposium Workshops, NOMS, 2008, pp. 52–55.
- [10] Y.-Y. A K.-W. Lee, D.-W. Kum, S.-H. Lee, Y.-Z. Cho, B. Yae, W.-Y. Jung, Enhanced fast handover mechanism using MIH services in MIPv6, in Wired/ Wireless Internet Communications, 2006, pp. 120–131.
- [11] RFC 4608, Fast Handover for Mobile IPv6, IETF, 2016.
- [12] Q.B. Mussabbir, Y. Wenbing, N. Zeyun, F. Xiaoming, Optimized FMIPv6 using IEEE 802.21 MIH services in vehicular networks, IEEE Transactions on Vehicular Technology 56 (2007) 3397–3407. RFC 4960, Stream Control Transmission Protocol, IETF, 2007.
- [13] R. Rouil, N. Golmie, N. Montavont, Media independent handover transport using cross-layer optimized stream control transmission protocol, Comput. Commun. 33 (2010) 1075–1085.
- [14] C. Yung-Mu, L. Min-Yen, L. Shao-Chieh, C. Shao-Chen, C. Tein-Yaw, SCTP-based handoff based on MIH triggers information in campus networks, in Eighth International Conference on Advanced Communication Technology, ICACT, 2006, pp. 1297–1301.
- [15] RFC 5061, Stream Control Transmission Protocol (SCTP) Dynamic Address Reconfiguration, IETF, 2007.
- [16] <<http://tools.ietf.org/html/draft-riegel-tuexen-mobile-sctp-052010>>, visited in September 2010.
- [17] E. Fallon, L. Murphy, J. Murphy, Optimizing metropolitan area wireless path selection using Media Independent Handover, in Second International Workshop on Cross Layer Design (IWCLD „09), 2009, pp. 1–5.
- [18] RFC 3261, SIP: Session Initiation Protocol, IETF, 2002.
- [19] J. Young-Chul, K. Byung-Kil, K. Young-Tak, SIP Based End-to-End QoS negotiation scheme for MIH, in Second IEEE/IFIP International Workshop on Broadband Convergence Networks (BcN „07), 2007, pp. 1–12.
- [20] T. Al Mosawi, D. Wisely, H. Aghvami, A novel micro mobility solution based on Media Independent Handover and SIP, in IEEE 64th Vehicular Technology Conference, 2006, pp. 1–5.
- [21] RFC 3312, Integration of resource management and Session Initiation Protocol, IETF, 2002.
- [22] Y.C. Yee, K.N. Choong, A.L.Y. Low, S.W. Tan, SIP-based proactive and adaptive mobility management framework for heterogeneous networks, Journal of Network and Computer Applications 31 (2008) 771–792.
- [23] H. Chung-Ming, L. Chao-Hsien, T. Po-Han, Multihomed SIP-based network mobility using IEEE 802.21 Media Independent Handover, in IEEE International Conference on Communications (ICC „09), 2009, pp. 1–5.